

VERDEGAAL BROTHERS'

SULFURIC ACID

AGRICULTURAL
PRODUCTS
DATA SHEET

GUARANTEED ANALYSIS:

Sulfur (S)..... 31%

Derived from Sulfuric Acid

PROPERTIES:

Weight per gallon 15.4 lbs.

Gallons per ton 130 gal.

Percent Sulfuric Acid..... 93%

Sulfur equivalent from sulfuric acid 31%

Crystallization temperature..... 98° @ 39° F

93° @ -16.6° F

pH..... less than 1

EQUIPMENT FOR HANDLING:

Use hoses approved for sulfuric acid when transferring material. Field storage polyethylene tanks must have extra heavy walls and rated for over

15.4 pounds per gallon material. Mild steel or stainless steel tanks may also be used for storage. Sulfuric acid attacks many metals, releasing hydrogen.

NON NUTRITIVE ELEMENTS:

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.aapfco.org/metals.htm>

TRANSPORTATION:

Shipments must be shipped RQ, Sulfuric Acid, Class 8, UN1830, Packing Group II, Corrosive.

SAFETY:

Keep unauthorized personnel away from this product. Never add water to sulfuric acid. A exothermic reaction with splattering will occur.

An exception is that small amounts of sulfuric acid may be diluted with a large volume of water if not in an enclosed space. If under pressure, explosive hydrogen gas is present.

PERSONAL PROTECTION:

Wear hardhat, face shield, rubber protective gloves, clothing and footwear when handling this material. Wear respiratory protection

when exposed to acid mist. Emergency safety shower and eye wash should be available.

FIRST AID:

Skin contact causes severe irritation and burns. Do not get in eyes, on skin or clothing. In case of skin contact, remove affected clothing and flood with water, then cover skin with moist sodium bicarbonate (baking soda) or sterile neutralizing solution. Speed in removing

material from skin is of extreme importance. If acid is swallowed, do not induce vomiting. Give milk or white of eggs beaten with water or water to dilute the acid. In case of eye contact, immediately flush with plenty of water for at least 15 minutes. Get medical attention at once.

The recommendations of Verdegaal Brothers, Inc., for the use of the material described herein, or any apparatus in handling the material, are based upon tests believed to be reliable. However, Verdegaal Brothers, Inc., makes no guarantee of the results to be obtained and assumes no liability therewith; nor is said company to be held liable for any personal injury or property damage or other type

of loss resulting from the storage, handling or use of the material described herein or its admixture with any other material, in as much as the application of the material or the operation of the equipment is not under its direct control; nor are these to be taken as a license to operate under, or recommendations to infringe, any patent.



VERDEGAAL BROTHERS, INC.

13555 S. 11th. Ave. / Hanford, CA 93230-9591

PH. (559) 582-9205 • FAX (559) 582-4274 • (888) 742-8728

Email: verdegaal@verdegaalbrothers.com

Webpage: www.verdegaalbrothers.com